



ATEX

CFC & HCFC
FREE

50Hz./ 60Hz.



Features

- **Power supply:** (380-420 VAC 50Hz) or (440-480 VAC 60Hz) + Neutral + Earth.
- **Available power:** from 2,6 to 5,3 Kw.
- **Structure:**
 - Vertical structure compact for easy mounting directly on a wall.
 - AISI-304 stainless steel resistant to external weather conditions.
 - Structure, covered and air system thermal insulated.
 - Accessible stainless steel covered.
- **Air circuit:**
 - Flame-proof axial fan.
 - High filtering power ATEX certified air filters with easy removal and cleaning.
- **Cooling circuit:**
 - Semi-hermetic compressor with triple protection, certified for hazardous areas and pipe assembly using stainless steel vibration suppressors.
 - Air exchangers built with copper pipes and aluminum fins.
 - Explosion-proof solenoid valve
 - Safety valve.
 - Liquid line filter drier.
 - Explosion-proof condensation fan.
 - Electric control with adaptation to extreme weather conditions.
- **Interface:**
 - Adjustable temperature thermostat.
 - Control panel:
 - Green led light for power supply.
 - Green led light for each engine running.
 - Red led light for alarm and reset push button.
 - Operation selector.
 - Input signal on-off remote.
 - Output signal alarm.